

PRODUCT DATA SHEET

SA Nail Base

SA43NB

Base Membrane
SBS Modified Bitumen • Fiberglass Reinforced
Polyolefin Film Surface



USAGE: Base Sheet
APPLICATION: Mechanically Fastened
PACKAGING: Paper Wrapped or Boxed
25 rolls/pallet

	UNIT	STANDARD		SA43NB		
		ASTM-D4601				
		Type 1	Type 2			
Reinforcement	-	Fiberglass Mat (Non-Woven, Asbestos-Free)				
Top Surfacing	-	Polyolefin Film				
Bottom Surfacing	-	Sand				
Roll Coverage	Squares	2 Overall AREA: 214 square feet				
Lay Lines	inches	2 - 4 - 6 - 19				
Roll Weight	lbs	-	-	88		
Roll Length	ft + inches	-	-	64' 9"		
Roll Width	inches	-	-	39.75		
Thickness	mil	-	-	65		
Net Mass	lbs/100ft ²	13.4	15.5	41		
Mass of Desaturated Glass Mat	lbs/100ft ²	1.4	1.7	> 1.75		
Peak Load at 23°C	MD	lbs/in	22	44	MD	65
	CD				CD	48
Elongation at Peak Load at 23°C	MD	%	-	-	MD	4
	CD				CD	3
Ultimate Elongation at 23°C	MD	%	-	-	MD	34
	CD				CD	40
Tear Strength at 23°C	MD	lbf	-	-	MD	92
	CD				CD	80
Pliability	½" Radius		PASS	PASS	MD	PASS
	¾" Radius				CD	PASS
Low Temp Flexibility	MD	°C	-	-	MD	-35
	CD				CD	-35
Dimensional Stability	% max	-	-	< 0.12		
Compound Stability	°C	-	-	102		
Liquid Water Transmission (D4869)	4 hrs min	-	-	PASS		

Ultimate Elongation is reported at point where load has dropped down to 5% of its original peak.

ADDITIONAL INFORMATION					
LEED®	Recycled Content: 0%				
	Production Location:				
	Fresno, California U.S.A.				



188 S. Teilman Avenue Fresno, California 93706-1334 U.S.A.
Toll Free: 800-621-9281 Fax: 559-233-4607 www.mbtechnology.com

WARNING: This product can expose you to chemicals including benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
ADVERTENCIA: Este producto puede exponerle a químicos incluyendo benzene, que es conocido por el Estado de California como causante de cáncer y defectos de nacimiento u otros daños reproductivos. Para mayor información visite www.P65Warnings.ca.gov

