

# PRODUCT DATA SHEET

## selfStick SA Base/Ply

### SA65FF

SBS Modified Bitumen • Fiberglass Reinforced • Polyolefin Film Surface  
Split Back Release Film • Ideal for Use Under SA or Torch Applied Cap Membrane



USAGE: Base / Ply APPLICATION: Self Adhering PACKAGING: Paper Wrapped 25 rolls/pallet	UNIT	STANDARD			SA65FF		
		ASTM-D1970	ASTM-D4601				
			Type 1	Type 2			
Reinforcement	-	<b>Fiberglass Mat</b> (Non-Woven, Asbestos-Free)					
Top Surfacing	-	<b>Polyolefin Film</b>					
Bottom Surfacing	-	<b>SBS Modified Asphalt</b> Protected with Split-Back Release Film					
Roll Coverage	Squares	<b>2</b> Overall AREA: 215 square feet					
Lay Lines	inches	<b>3</b>					
Roll Weight	lbs	-	-	-	<b>71</b>		
Roll Length	ft + inches	-	-	-	<b>65' 0"</b>		
Roll Width	inches	-	-	-	<b>39.750</b>		
Thickness	mil	40	-	-	<b>58</b>		
Net Mass	lbs/100ft <sup>2</sup>	-	13.4	15.5	<b>33</b>		
Peak Load at 23°C	MD	lbs/in	25	22	44	<b>MD</b>	<b>51</b>
	CD					<b>CD</b>	<b>44</b>
Elongation at Peak Load at 23°C	MD	%	-	-	-	<b>MD</b>	<b>3</b>
	CD					<b>CD</b>	<b>4</b>
Ultimate Elongation at 23°C	MD	%	10	-	-	<b>MD</b>	<b>42</b>
	CD					<b>CD</b>	<b>39</b>
Tear Strength at 23°C	MD	lbf	20	-	-	<b>MD</b>	<b>88</b>
	CD					<b>CD</b>	<b>75</b>
Pliability	1/2" Radius		-	PASS	PASS	<b>MD</b>	<b>PASS</b>
	3/4" Radius					<b>CD</b>	<b>PASS</b>
Low Temp Flexibility	MD	°C	-29	-	-	<b>MD</b>	<b>-42</b>
	CD					<b>CD</b>	<b>-42</b>
Dimensional Stability	% max	-	-	-	<b>&lt; 0.12</b>		
Thermal Stability (max)	inches	0.1	-	-	<b>&lt; 0.05</b>		
Adhesion to Plywood @ 75°F	lbf/ft width	12.0	-	-	<b>&gt; 40</b>		

Ultimate Elongation is reported at point where load has dropped down to 5% of its original peak.

ADDITIONAL INFORMATION					
LEED®	Recycled Content: 0%				
	Production Location:				
	Fresno, California U.S.A.				



188 S. Teilman Avenue Fresno, California 93706-1334 U.S.A.  
Toll Free: 800-621-9281 Fax: 559-233-4607 www.mbtechnology.com

**WARNING:** This product can expose you to chemicals including benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov  
**ADVERTENCIA:** Este producto puede exponerle a químicos incluyendo benzeno, que es conocido por el Estado de California como causante de cáncer y defectos de nacimiento u otros daños reproductivos. Para mayor información visite www.P65Warnings.ca.gov



MBT