PRODUCT DATA SHEET

metalflexSBS

MF160WCU Copper

Fire Rated SBS Modified Cap Sheet Copper Foil Surface High Tensile Strength Fiberglass Scrim Reinforced







 Subject to the conditions of Approval as a roof cover when installed as described in RoofNav.



USAGE: Cap Sheet / Flashing APPLICATION: Heat Weld, Hot Asphalt PACKAGING: Paper Wrapped 25 rolls/pallet Reinforcement		UNIT	STANDARD						
			ASTM-D6298	ASTM	-D6163 G Type 2	rade S Type 3	MF160WCU (Non-Woven, Asbestos-Free)		
			High Tensil						
		_	High Tensile Strength Fiberglass Scrim (Non-Woven, Asbestos-Free) Copper Foil (99.9% minimum CU)						
Top Surfacing		-	Sand						
Bottom Surfacing		Squares							
Roll Coverage		inches	1 Overall AREA: 110 square feet 3.625						
Selvage Width		lbs	3.023				1	13	
Roll Weight		ft + inches	-	-	-	-		4"	
Roll Length Roll Width		inches	-	-	-	-			
	Thickness		134	80	80	80		48	
Net Mass		mil lbs/100ft ²	80	45	45	45		10 02	
Peak Load at 23°C	MD	103/ 10011	85	30	80	150	MD	116	
	CD	lbs/in					CD	120	
Peak Load at -18°C	MD	lbs/in	160	70	150	180	MD	184	
	CD						CD	183	
Elongation at Peak Load at 23°C	MD	%	5	2	4	3	MD	6	
	CD						CD	8	
Elongation at Peak Load at -18°C	MD	%	3	1	2	2	MD	5	
	CD						CD	6	
Ultimate Elongation at 23°C	MD	%	25	3	40	2	MD	45	
	CD	70					C	54	
Tear Strength at 23°C	MD	─ lbf	120	35	110	210	MD	228	
	CD						CD	249	
Low Temp Flexibility	MD	°C	-18	-18	-18	-15	MD	-18	
	CD						CD	-18	
Dimensional Stability		% max	0.2	0.5	0.5	0.5	0.1		
Compound Stability		°C	107	102	102	91	107		
Cyclic Therma	Cyclic Thermal Shock		0.2	-	-	-	0.	08	

Ultimate Elongation is reported at point where load has dropped down to 5% of its original peak.

ADDITIONAL INFORMATION									
	Recycled Content: 0%		Solar Reflectance	Thermal Emittance	(SRI)				
LEED®	Production Location:		ASTM-E903	ASTM-E408	Solar Reflective Index				
	Fresno, California U.S.A.	MF160WCU Copper	0.74	0.05	65				

Values are for Reference Only. Not tested to C1549 / C1371.



188 S. Teilman Avenue Fresno, California 93706-1334 U.S.A.
Toll Free: 800-621-9281 Fax: 559-233-4607 www.mbtechnology.com

MARNING: This product con expose you to chemicals including benzene, which is known to the Strate of California to cause center and birth defects or other reproductive harm. For more information go to www.P65VManings.ca.gov

↑ ADVERTENCIA: Exte producto posed exponent a quinticos incluyendo benzene, que es concidio por el Estado de California como cousenta de cóncer y defectos de nocimiento u otros daños reproductivos. Para mayor información visite www.P65VManings.ca.gov

